

## WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

WO 97/45523 (51) International Patent Classification 6: (11) International Publication Number: A1 C11D 7/54, 7/32 4 December 1997 (04.12.97) (43) International Publication Date: (81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, PCT/NL97/00294 (21) International Application Number: BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, 26 May 1997 (26.05.97) (22) International Filing Date: LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO. NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ARIPO patent (GH, KE, LS, (30) Priority Data: MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, 29 May 1996 (29.05.96) 1003225 MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, (71) Applicants (for all designated States except US): HEINEKEN SN, TD, TG). TECHNICAL SERVICES B.V. [NL/NL]; 2e Weteringplantsoen 21, NL-1017 ZD Amsterdam (NL). LHS MICRO-FILTRATIONS B.V. [NL/NL]; Opaalstraat 22, NL-7554 TS Published Hengelo (NL). With international search report. Before the expiration of the time limit for amending the (72) Inventors; and claims and to be republished in the event of the receipt of (75) Inventors/Applicants (for US only): MOL, Martinus, Nicolaas, amendments. Maria [NL/NL]; Turfmarkt 3, NL-2312 CD Leiden (NL). In English translation (filed in Dutch). VAN HOOF, Stephan, Cornelus, Johannes, Maria (NL/NL); Troelstraweg 167, NL-6702 AK Wageningen (NL). (74) Agent: SMULDERS, Th., A., H., J.; Vereenigde Octrooibureaux, Nieuwe Parklaan 97, NL-2587 BN The Hague (NL).

(54) Title: METHOD FOR CLEANING ITEMS IN PARTICULAR FILTERS, USED DURING FOODSTUFF PRODUCTION

(57) Abstract

The invention relates to a method for cleaning apparatus used during the production of foodstuffs, in particular the filtration thereof, wherein this apparatus is contacted after use with a cleaning system based on the combination of a cyclic nitroxyl compound and a hypohalite.

### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Amenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	· Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	U <b>Z</b>	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG.	Congo	KE	Кепув	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	K2	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	u	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		
ı							

10

15

20

25

# METHOD FOR CLEANING ITEMS IN PARTICULAR FILTERS, USED DURING FOODSTUFF PRODUCTION

The invention relates to the cleaning of apparatus used during the production, processing or treatment of foodstuffs, more in particular the filtering thereof. An important example thereof is the cleaning of apparatus for brewing beer and more in particular the cleaning of filters, such as membrane filters for filtering residual beer and settled beer. Within the context of this invention the term "production" is used to indicate all treatments carried out on foodstuffs, such as production, treatment, processing and the like.

During the production of foodstuffs, such as milk (products), fruit juices, beer, soft drinks (such as lemonades), cider, wine, sherry, port, distilled drinks and the like, the problem often occurs that apparatus must be cleaned after a certain period, because components from the material to be treated are adsorbed or absorbed or precipitate on surfaces of the apparatus, which is undesirable. This may in fact give rise to a disturbance of, on the one hand, the operation of the apparatus and, on the other hand, the quality of the final product.

The apparatus involved is the apparatus used during the treatment of foodstuffs, more in particular liquids, as indicated above. More in particular, filters are involved, such as membrane filters used for filtering the above products or semimanufactures therefor.

Examples of such treatments are the production and/or processing of milk and milk products, fruit juices, beer, soft drinks, cider, wine, sherry, port, distilled drinks and the like.

In the case of brewing beer the invention relates to, inter alia, the apparatus used during the preparation of malt, the conversion of malt and/or unmalted grain into wort and the further processing of the wort, with or without

WO 97/45523

5

10

15

20

25

30

35

addition of extra components, such as hops, by fermentation to beer, as well as all auxiliary apparatus used therewith and coming in contact with main or secondary streams from these processes.


An example of the disturbance of the operation of the apparatus is found with the different filters used, e.g. the filters for filtering soft drinks, milk (products), wine, sherry, port, distilled drinks, fruit juices, lemonade, beer, such as settled beer, residual beer, but also the wort/spent grain separation, hot trub separation and cold trub separation.

The capacity of filters used in such processes, the flux, decreases in the course of time, which is of course undesirable. This particularly plays a role when use is made of membrane filters. This capacity decrease can be partly inhibited by rinsing back the filter. After some time, however, this is not sufficient, and it is therefore necessary to clean the filter.

A further examination has revealed that the apparatus, and more in particular the filters, become contaminated by a combination of all kinds of compounds, of which polysaccharides, oligosaccharides, proteins,  $\beta\text{-glucanes},$  fats and polyphenols are important components. during the production

Conventional cleaning techniques, e.g. based on catalyzed or uncatalyzed oxidation, e.g. with a peroxide/metal (manganese) complex hypochlorite or hypobromite, are not satisfactory, which appears from the fact that the flux cannot be restored to the original value or close thereto. Nor does the use of detergents or enzymes, such as proteases, carbohydrases, amylases, pullulanases, proteases and lipases, lead to the desired results.

There is therefore a need for an efficient cleaning system for cleaning apparatus for the production, as defined above, of liquid foodstuffs, which system is capable of effecting a proper cleaning, which must preferably be done



15

20

25

30

35

within a short time (15-120 min) and during which substantially all contaminations are removed.

The invention is based on the surprising insight that it is possible to adequately clean apparatus used during the production of foodstuffs by using a cleaning system on the basis of a combination of a cyclic nitroxyl compound and a hypohalite. This involves removal of contaminations formed during the production of foodstuffs, e.g. precipitated on surfaces of the apparatus or in pores of filters.

The invention therefore relates to a method for cleaning apparatus used during the production of foodstuffs, in which this apparatus is contacted after use with a cleaning system based on the combination of a cyclic nitroxyl compound and a hypohalite in aqueous solution.

Preferably, the cyclic nitroxyl compound is a substituted piperidine, such as 2,2,6,6-tetra-methylpiperidine-N-oxyl (TEMPO). This is a commercially available compound (CAS Reg. No. 2564-83-2).

In combination with a hypohalite, preferably a hypobromite, it is possible to obtain a rapid removal of contaminations by using catalytic amounts of TEMPO. The hypobromite, which is preferred, is preferably formed in situ from hypochlorite and alkali metal bromide (most preferably NaBr), so that the reaction system of Fig. 1 is obtained. It is to be noted that preference is given to the use of bromite, since it gives a considerably shorter cleaning time than the chlorite. It is also possible to generate the bromite from other components or to add it as such to the system.

The method according to the invention is most preferably carried out by contacting an aqueous solution of the nitroxyl compound, such as the different nitroxide radicals, e.g. 2,2,6,6-tetra-methylpiperidine-N-oxyl (TEMPO), 4-oxo-2,2,6,6-tetra-methylpiperidine-N-oxyl (OTEMPO), 4-hydroxy-2,2,6,6-tetra-methylpiperidine-N-oxyl (TEMPOL) and other derivatives having the same 2,2,6,6-tetra-

10

15

20

25

30

35

methylpiperidine-N-oxyl (TEMPO) skeleton, as well as derivatives on the basis of 4,4-dimethyloxazolidine-N-oxyl (DOXYL) and 2,2,5,5-tetra-methylpyrrolidine-N-oxyl (PROXYL) and the hypohalite in water with the contaminated apparatus.

The concentration of the cyclic nitroxyl compound preferably ranges between 1 and 250 mg/l, more in particular between 2 and 25 mg/l. Such concentrations of nitroxyl compound can be properly combined with hypohalite (OBr or OCl) concentrations of at least 0.5 g/l, preferably 0.75 to 10 g/l. In case a system on the basis of hypochlorite, alkali metal bromide and the nitroxyl compound is used, the amount of bromide is significantly lower than the amount of hypochlorite. Since the bromite is regenerated, bromide contents (calculated as Br) of not more than 1 g/l are sufficient at the above concentrations of the nitroxyl compound.

In a characteristic method a catalytic amount of TEMPO is used. Only minute amounts of the cyclic nitroxyl compound are necessary, since it functions as a catalyst for forming the active oxidant, the hypohalite, from hypohalide.

It is to be noted in this respect that the present system of cyclic nitroxyl compound and hypohalide is known per se, e.g. from WO-A 95/07303. This publication describes the oxidation of carbohydrates with primary hydroxyl groups. In no manner, however, does it appear therefrom that this system is useful for cleaning apparatus used for the production of foodstuffs, in which the nature of the contaminations is as different as indicated above. This is the more surprising as the conventional cleaning methods on the basis of hypohalite, e.g. with filters when brewing beer, do not give the desired effect.

The invention is applicable to all apparatus used during the processing of foodstuffs, and which contacts the main stream and/or the secondary streams of the production. More in particular, the invention is applicable to the cleaning of filters used for filtering milk, milk products,



10

15

20

25

30

35

soft drinks, cider, wine, sherry, port, fruit juices, distilled drinks, beer, settled beer, residual beer, but also the wort/spent grain separation, hot trub separation and cold trub separation.

The contact between cleaning liquid and apparatus may be effected both statically and dynamically, that is to say: the liquid either is stationary or flows through the apparatus. Suitable contact times range between 5 minutes and 2 hours, which times of course also depend on the degree of contamination, the concentration of the components (more in particular the nitroxyl compound) and the temperature.

The pH of the cleaning liquid is preferably kept within the alkaline range. In practice, this is a value ranging between 7 and 12. When using only hypochlorite in combination with the nitroxyl compound, even weakly acid pH values are possible (pH>6). Since the cleaning is often accompanied with the formation of organic acids, the cleaning can be controlled by means of the amount of caustic required to maintain the adjusted pH. As soon as the caustic consumption strongly decreases, also after dosing HOCl/HOBr, it can be noticed that the cleaning is terminated. This system has the great advantage that a low concentration of oxidant is sufficient, so that damage to apparatus and parts can be decreased or even completely avoided.

After cleaning the apparatus is rinsed and can be used again. It is to be noted that the system according to the invention can be suitably used for each cleaning. It is also possible, however, to alternately clean the apparatus with, on the one hand, a conventional system, e.g. based on detergents, optionally in combination with peroxides and/or enzymes, and, on the other hand, the system according to the invention. It is also possible to use the system according to the invention as a kind of postcleaning, subsequent to a conventional system.

The invention will now be explained by means of some, non-limitative, examples.

### EXAMPLE 1

By means of a module for filtering settled beer, which was provided with a non-used membrane filter, settled beer was filtered for some time at a pressure of 0.3 bar. The flux of the beer was determined at a number of times (A).

Then the filter was cleaned for 2 hours with a solution containing 4.5 g/l HOCl, 35 mg/l NaBr and 15 mg/l TEMPO. After the cleaning the test was repeated (B).

This cycle was then carried out one more time (C). In the following table some results are listed.

Table

15	Flux	(1/hour/bar/m²)

Time	(min)	A	В	С
20		1100	1100	1400
30		850	1050	1100



#### Claims

- 1. A method for cleaning apparatus, more in particular a filter, used during the production of foodstuffs, wherein said apparatus is contacted after use with a cleaning system based on the combination of a cyclic nitroxyl compound and a hypohalite.
- 2. A method according to claim 1, wherein apparatus, more in particular a filter used for producing (filtering) milk (products), fruit juices, beer, soft drinks, such as lemonades, cider, wine, sherry, port, distilled drinks and the like, more in particular beer, is cleaned.
- 3. A method according to claim 1 or 2, wherein a membrane filter is cleaned.
  - 4. A method according to claims 1-3, wherein the cyclic nitroxyl compound is used in a catalytic amount.
- 15 5. A method according to claims 1-4, wherein the cyclic nitroxyl compound used is 2,2,6,6-tetra-methylpiperidine-N-oxyl (TEMPO), 4-oxo-2,2,6,6-tetra-methylpiperidine-N-oxyl (OTEMPO), 4-hydroxy-2,2,6,6-tetra-methylpiperidine-N-oxyl (TEMPOL) and other derivatives having the same 2,2,6,6-tetra-
- methylpiperidine-N-oxyl (TEMPO) skeleton, as well as derivatives on the basis of 4,4-dimethyloxazolidine-N-oxyl (DOXYL) and 2,2,5,5-tetra-methylpyrrolidine-N-oxyl (PROXYL), more in particular 2,2,6,6-tetra-methylpiperidine-N-oxyl (TEMPO).
- 25 6. A method according to claims 1-5, wherein the hypohalite used is a hypobromite.
  - 7. A method according to claims 1-6, wherein the hypohalite used is a combination of hypochlorite and an alkali bromide.
- 30 8. A method according to claims 1-7, wherein the cleaning system is used as an aqueous solution.




- 9. A method according to claims 1-8, wherein said cleaning is preceded by a cleaning with another cleaning system.
- 10. A method for producing one or more foodstuffs, more in particular beer, in suitable apparatus, wherein said apparatus is regularly cleaned using the method according to any or more of claims 1-9.
- 11. The use of a cleaning system based on the combination of a cyclic nitroxyl compound, preferably in combination with a hypohalite, for cleaning apparatus used for the production, more in particular the filtering, of foodstuffs.

Interr 1al Application No PCT/NL 97/00294

CLASSIFICATION OF SUBJECT MATTER PC 6 C11D7/54 C111 IPC 6 C11D7/32 According to international Patent Classification (IPC) or to both national classification and IPC B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 6 C11D Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practical, search terms used) C. DOCUMENTS CONSIDERED TO BE RELEVANT Relevant to claim No. Citation of document, with indication, where appropriate, of the relevant passages 1,8 DATABASE WPI Α Section Ch, Week 9323 Derwent Publications Ltd., London, GB; Class A97, AN 93-186697 XP002024217 & RO 104 553 A (DERO INTR DETERGENTI) , 25 February 1992 see abstract 1 DE 36 35 357 A (WELLHOENER VEIT) 21 April Α see the whole document 1 - 3.9EP 0 392 395 A (GESSNER & CO GMBH) 17 Α October 1990 see page 9, line 20 - line 25; claims 1,29 Patent family members are listed in annex. Further documents are listed in the continuation of box C. X Special categories of cited documents : Ister document published after the international filing date or priority date and not in conflict with the application but ofted to understand the principle or theory underlying the \*A\* document defining the general state of the art which is not considered to be of particular relevance invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to "E" earlier document but published on or after the international filing date involve an inventive step when the document is taken alone "L" document which may throw doubts on priority olaim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such docu-"O" document referring to an oral disclosure, use, exhibition or ments, such combination being obvious to a person skilled in the art. \*P\* document published prior to the international filing date but "&" document member of the same patent family tater than the priority date claimed Date of mailing of the international search report Date of the actual completion of the international search 17.10.97 9 October 1997 Authorized officer Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentiaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Grittern, A

Form PCT/ISA/210 (second sheet) (July 1992)

1



"itormation on patent family members

PCT/NL 97/00294

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
DE 3635357 A	21-04-88	NONE	
EP 0392395 A	17-10-90	DE 3911697 A JP 3117475 A	25-10-90 20-05-91